



COMPACT DOME



Fixed lens compact dome with IR



Versatile, lightweight, and fit for discreet indoor installations



High resolution (5MP) and extreme low light performance (f/1.3)



Built-in AI video and audio analytics and on-device storage



Factory-installed certificates backed by a trusted platform module (TPM)



Designed and developed in Norway and the UK

Image sensor 5MP (4:3)

Image sensor size format 1/2.7"

Lens Focal length: 3.2mm Aperture: *f*/1.3 Fixed focus

IR night vision Automatic night mode IR range: 10m 850 nm IR LED

Minimum illumination in color mode 0.10lux

Field of view 102° Horizontal 71° Vertical

Maximum resolution & Frame rate 2688x1944@30fps

Dynamic range Multi-exposure line-based HDR

Video compression H.265, H.264, Motion JPEG

Audio

Microphone Audio classification

Security Trusted Platform Module (TPM 2.0) Factory-installed certificates No default passwords Mandatory access authentication HTTPS/TLS encryption

Network protocols IPv4, HTTPS, TLS, DNS, mDNS, DNS-SD, NTP, RTSP, RTP, RTCP, ICMP, DHCP, ARP Streaming: RTP/UDP, RTP/RTSP/HTTPS/TCP Power source PoE 802.3af USB-C, installation only

Power consumption Typical: 5W Max: 8W

Storage 2x MicroSD, SDXC UHS-I

Connection 802.3ab 10/100/1000 Gigabit Ethernet USB-C for preview and setup

Installation aid Mount template Screws and wall plugs included 1/4-20 UNC standardized camera mount thread

Adjustment range Pan, Tilt, Roll

Temperature Operating: 0°C to +40°C Storage: -40°C to +60°C

Physical characteristics Dimensions: 107x107x64mm Weight: 280g


EMC

EN 55032, EN 61000-3-2/-3, EN 61000-6-4, IEC 61000-4-2/-3/-4/-5/-6/-8, CISPR 32, AS/NZS CISPR 32, FCC Part 15B, ICES-003 Issue 6


Safety IEC62368-1, UL62368-1, IEC62471

Technical drawings

Side view



Bottom view



Ordering information

Ava Compact Dome

Product ID	Onboard retention	Deployment	Color
COMPACTDOME-W-5MP-30	30 days	Aware Cloud	White
COMPACTDOME-B-5MP-30	30 days	Aware Cloud	Black
COMPACTDOME-W-5MP-60	60 days	Aware Cloud	White
COMPACTDOME-B-5MP-60	60 days	Aware Cloud	Black
COMPACTDOME-W-5MP-120	120 days	Aware Cloud	White
COMPACTDOME-B-5MP-120	120 days	Aware Cloud	Black
COMPACTDOME-W	No	Aware on-prem	White
COMPACTDOME-B	No	Aware on-prem	Black